

OUTRIGGERS FULLY EXTENDED TO 6.00M CENTRES

LIFTING CAPACITIES - 360° SLEW

L.M.I. CODE	# 0001						
RADIUS IN METRES	BOOM LENGTH IN METRES						
	9.20	13.00	16.12	20.00	23.50	27.00	30.00
3.00	30.00	24.40	17.15				
3.50	24.15	22.55	17.15				
4.00	21.35	20.75	17.15	13.75			
4.50	18.65	18.40	16.65	13.75			
5.00	16.50	16.25	15.55	13.30	12.05		
6.00	13.25	13.00	12.85	11.80	10.85	9.40	7.50
7.00	10.90	10.65	10.55	10.65	9.80	8.60	@ 7.25M
8.00	SEE WARNING NOTE 15	8.90	8.80	9.20	8.90	7.85	7.00
9.00		7.10	7.00	7.45	7.75	7.30	6.45
10.00		5.75	5.65	6.10	6.40	6.60	5.95
12.00			3.80	4.25	4.50	4.70	4.85
14.00			2.60	3.00	3.30	3.45	3.60
16.00				2.15	2.40	2.60	2.70
18.00					1.75	1.95	2.05
20.00					1.25	1.40	1.55
22.00						1.00	1.15
24.00						0.70	0.80
26.00							0.55
12° ANGLE CAPACITIES	10.00	4.75	2.60	1.55	1.00	0.60	0.35
(REF RAD)	(7.20)	(11.00)	(14.00)	(17.80)	(21.20)	(24.70)	(27.60)

L.M.I. OPERATING CODE REFER TO L.M.I. MANUAL FOR INSTRUCTIONS.

AT635/L/DIN/3.475/0995/01

